

1. Identification

Product identifier **CSS-1S**
Other means of identification None.
Recommended use Not available.
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information
Manufacturer: Ergon Asphalt & Emulsions, Inc.
Address: 2829 Lakeland Drive
 Jackson, MS 39232
Website: www.ergonasphalt.com
Telephone: 1-800-222-7122 (Customer Service)
E-mail: sds@ergon.com
24 hour Emergency (CHEMTREC): North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Carcinogenicity Category 2
 Specific target organ toxicity, repeated exposure Category 2
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Warning
Hazard statement May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer.
Precautionary statement
Prevention Do not breathe dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response Get medical advice/attention if you feel unwell.
Storage Store locked up.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H₂S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	40 - 60
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	1 - 10

Chemical name	Common name and synonyms	CAS number	%
KEROSINE (PETROLEUM), HYDRODESULFURIZED		64742-81-0	1 - 10
HYDROCHLORIC ACID		7647-01-0	< 1
NAPHTHALENE		91-20-3	< 1

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of asphalt. Wash contact areas with soap and water. If needed, seek medical attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed:
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.
Specific methods	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m ³
		5 ppm
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m ³
		10 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fume.
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	2 ppm	
KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)	TWA	200 mg/m ³	Non-aerosol.
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m ³	Fume.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	100 mg/m ³	
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m ³	
		5 ppm	
KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)	TWA	100 mg/m ³	
NAPHTHALENE (CAS 91-20-3)	STEL	75 mg/m ³	
		15 ppm	
	TWA	50 mg/m ³	
		10 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0) Can be absorbed through the skin.

NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses; chemical goggles (if splashing is possible).
Skin protection	
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact. Plastic or rubber gloves, apron and boots.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Brown to black in color.
Physical state	Liquid.
Form	Liquid.
Color	Black
Odor	Tar-like
Odor threshold	Not available.
pH	2.1 - 4
Melting point/freezing point	150 - 180 °F (65.56 - 82.22 °C)
Initial boiling point and boiling range	>= 212 °F (>= 100 °C)
Flash point	> 212.0 °F (> 100.0 °C) Cleveland Open Cup
Evaporation rate	< 1
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 1 mm Hg @ 70C
Vapor density	> 1
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 700 °F (> 371.11 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	1.03

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport
-------------------	--

Chemical stability	Stable under normal temperature conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat product.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	May be irritating to eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
HYDROCHLORIC ACID (CAS 7647-01-0)		
Acute		
Dermal		
LD50	Mouse	1449 mg/kg
NAPHTHALENE (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation May be irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization	Not available.
Skin sensitization	May cause skin disorders if contact is repeated or prolonged.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
HYDROCHLORIC ACID (CAS 7647-01-0)	3 Not classifiable as to carcinogenicity to humans.
NAPHTHALENE (CAS 91-20-3)	2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.
---------------------------	--

Reproductive toxicity Not classified.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects	Prolonged exposure may cause chronic effects.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product		Species	Test Results
CSS-1S			
Aquatic			
Crustacea	EC50	Daphnia	1283.4127 mg/l, 48 hours estimated
Fish	LC50	Fish	45.686 mg/l, 96 hours estimated
Components		Species	Test Results
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
HYDROCHLORIC ACID (CAS 7647-01-0)			
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affinis)	282 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

NAPHTHALENE 3.3

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. No components are identified as hazardous wastes. Disposal recommendations are based on uncontaminated material.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Not applicable.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

Further information If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s. (Asphalt mixture), 9, PG III"

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4)	Listed.
HYDROCHLORIC ACID (CAS 7647-01-0)	Listed.
NAPHTHALENE (CAS 91-20-3)	Listed.

SARA 304 Emergency release notification

HYDROCHLORIC ACID (CAS 7647-01-0)	5000 LBS
-----------------------------------	----------

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
HYDROCHLORIC ACID	7647-01-0	5000	500		
Classified hazard categories	Specific target organ toxicity (single or repeated exposure) Hazard not otherwise classified (HNOC)				

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
NAPHTHALENE	91-20-3	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

HYDROCHLORIC ACID (CAS 7647-01-0)
NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROCHLORIC ACID (CAS 7647-01-0)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

HYDROCHLORIC ACID (CAS 7647-01-0)	6545
-----------------------------------	------

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

HYDROCHLORIC ACID (CAS 7647-01-0)	20 %WV
-----------------------------------	--------

DEA Exempt Chemical Mixtures Code Number

HYDROCHLORIC ACID (CAS 7647-01-0)	6545
-----------------------------------	------

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002
---------------------------	------------------------

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)

HYDROCHLORIC ACID (CAS 7647-01-0)
KEROSENE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)
NAPHTHALENE (CAS 91-20-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-11-2015

Revision date 10-22-2019

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings
Health: 2
Flammability: 1
Instability: 0

References
ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information This document has undergone significant changes and should be reviewed in its entirety