

## 1. Identification

**Product identifier** MC-3000P  
**Other means of identification** None.  
**Recommended use** Not available.  
**Recommended restrictions** None known.  
**Manufacturer/Importer/Supplier/Distributor information**  
**Manufacturer:** Ergon Asphalt & Emulsions, Inc.  
**Address:** 2829 Lakeland Drive  
 Jackson, MS 39232  
**Website:** www.ergonasphalt.com  
**Telephone:** 1-800-222-7122 (Customer Service)  
**E-mail:** sds@ergon.com  
**24 hour Emergency (CHEMTREC):** North America 1-800-424-9300; International 1-703-527-3887

## 2. Hazard(s) identification

**Physical hazards** Not classified.  
**Health hazards** Carcinogenicity Category 1B  
 Reproductive toxicity Category 2  
 Specific target organ toxicity, repeated exposure Category 2  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.  
**Label elements**



**Signal word** Danger

**Hazard statement** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause cancer.

### Precautionary statement

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection.  
**Response** If exposed or concerned: Get medical advice/attention.  
**Storage** Store locked up.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** Molten asphalt presents a thermal hazard.

**Supplemental information** Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H<sub>2</sub>S) can be harmful if inhaled.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	70 - 100

Chemical name	Common name and synonyms	CAS number	%
FUEL OIL, NO. 6		68553-00-4	0 - 40
Other components below reportable levels			1 - < 3

## 4. First-aid measures

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY. Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of the asphalt due to the risk of adhesion. Get immediate medical attention.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention or advice.
<b>Ingestion</b>	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Not available.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Foam. Dry powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Water. Do not use a solid water stream as it may scatter and spread fire. Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Fire may produce irritating, corrosive and/or toxic gases.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
<b>Specific methods</b>	In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them.
<b>Methods and materials for containment and cleaning up</b>	Extinguish all flames in the vicinity.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills in original containers for re-use.
<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not contaminate water. No special environmental precautions required. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

May be ignited by open flame. Keep away from sources of ignition - No smoking. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid contact with skin. Do not get this material on clothing. Wear personal protective equipment. Do not use in areas without adequate ventilation.

### Conditions for safe storage, including any incompatibilities

CAUTION The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Store in a well-ventilated place. Keep container tightly closed. Store in a closed container away from incompatible materials. Keep in an area equipped with sprinklers. Keep away from food, drink and animal feedings. Keep out of the reach of children. Use care in handling/storage.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Safety glasses. If risk of splashing, wear safety goggles or face shield.

#### Skin protection

##### Hand protection

Use gloves with long sleeves. When handling hot material, use heat resistant gloves.

##### Other

Thermally protective apron and long sleeves are recommended when volume of hot material is significant.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### Thermal hazards

During product use, there is a risk of thermal burns. Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Brown to black in color.

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Brown - black

### Odor

Aromatic Mild Petroleum Odor

### Odor threshold

Not available.

### pH

Not available.

### Melting point/freezing point

Not available.

### Initial boiling point and boiling range

320 - 550 °F (160 - 287.78 °C)

### Flash point

> 150.0 °F (> 65.6 °C)

### Evaporation rate

< 1

### Flammability (solid, gas)

Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 0.3 %

**Flammability limit - upper (%)** 5 %

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** < 50 psi

**Vapor density** > 4.5

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 490 °F (254.44 °C)

**Decomposition temperature** Not available.

**Viscosity** Not available.

**10. Stability and reactivity**

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** Risk of ignition. Material is stable under normal conditions.

**Possibility of hazardous reactions** Hazardous polymerization does not occur.

**Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

**11. Toxicological information****Information on likely routes of exposure**

**Inhalation** Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

**Skin contact** May be irritating to the skin.

**Eye contact** May be irritating to eyes.

**Ingestion** May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms related to the physical, chemical and toxicological characteristics** Not available.

**Information on toxicological effects**

**Acute toxicity** Not available.

**Skin corrosion/irritation** Not available.

**Serious eye damage/eye irritation** None known.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not available.

**Skin sensitization** None known.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** May cause cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

ASPHALT (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	Not available.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not available.
<b>Chronic effects</b>	Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects. Not expected to be hazardous by WHMIS criteria.
<b>Further information</b>	Symptoms may be delayed. This product has no known adverse effect on human health

**12. Ecological information**

<b>Ecotoxicity</b>	Not expected to be harmful to aquatic organisms.
--------------------	--

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
MC-3000P		
<b>Aquatic</b>		
Fish	LC50	Fish
		58.5889 mg/l, 96 hours estimated

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	Not available.
<b>Bioaccumulative potential</b>	Not available.
<b>Mobility in soil</b>	Not available.
<b>Other adverse effects</b>	Not available.

**13. Disposal considerations**

<b>Disposal instructions</b>	Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
<b>Contaminated packaging</b>	Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

**14. Transport information****DOT**

<b>UN number</b>	UN1999
<b>UN proper shipping name</b>	Tars, liquid
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Special precautions for user</b>	Not available.

**IATA**

<b>UN number</b>	UN1999
<b>UN proper shipping name</b>	Tars, liquid
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L

<b>Special precautions for user</b>	Not available.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

#### IMDG

<b>UN number</b>	UN1999
<b>UN proper shipping name</b>	Tars, liquid
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-E
<b>Special precautions for user</b>	Not available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not available.

#### DOT



#### IATA; IMDG



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

### SARA 311/312 Hazardous chemical

Yes

#### Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

### Safe Drinking Water Act (SDWA)

Not regulated.

## US state regulations

### California Proposition 65

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

FUEL OIL, NO. 6 (CAS 68553-00-4)

Listed: October 1, 1990

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

FUEL OIL, NO. 6 (CAS 68553-00-4)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	04-30-2014
Revision date	10-24-2019
Version #	03
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 2 Flammability: 1 Instability: 0

**References**

ACGIH  
EPA: AQUIRE database  
NLM: Hazardous Substances Data Base  
US. IARC Monographs on Occupational Exposures to Chemical Agents  
Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials)  
HSDB® - Hazardous Substances Data Bank  
IARC Monographs. Overall Evaluation of Carcinogenicity  
National Toxicology Program (NTP) Report on Carcinogens  
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices  
Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety