## SAFETY DATA SHEET



### 1. Identification

**Product identifier GAF Coating Shafter** 

Other means of identification

**Product Code** 1860

**Recommended use** Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Tricor Refining, LLC. **Manufacturer:** Address: P.O. Box 5877

Bakersfield, CA 93388

24-hour Telephone

(661) 393-7110

Number:

**CHEMTREC:** 1-800-424-9300 (North America) 1-703-527-3887 (International)

# 2. Hazard(s) identification

**Physical hazards** Not classified. **Health hazards** Not classified. **Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

\*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

**Label elements** 

None. **Hazard symbol** 

Signal word Not available. **Hazard statement** Not available.

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

**Storage** Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Molten asphalt presents a thermal hazard.

**Supplemental information** Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN

SULFIDE (H2S) can be harmful or fatal if inhaled.

#### 3. Composition/information on ingredients

#### **Mixtures**

# 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY.

Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of

the asphalt due to the risk of adhesion. Get immediate medical attention.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention or advice.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

**Most important** 

symptoms/effects, acute and

Material name: GAF Coating Shafter

delayed

Potential for severe thermal burns.

5895 Version #: 01 Issue date: 04-15-2015

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from

the chemical

Irritating and toxic gases or fumes may be released during a fire.

Special protective equipment and precautions for

firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective

clothing will only provide limited protection.

Fire-fighting

**Specific methods** 

equipment/instructions

ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may cause frothing.

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up

Dike far ahead of spill for later disposal. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal.

# 7. Handling and storage

Precautions for safe handling

Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place.

# 8. Exposure controls/personal protection

**Occupational exposure limits** 

No exposure limits noted for ingredient(s).

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering** 

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

## Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses. Wear face shield if there is risk of splashes.

**Hand protection** 

Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely,

wear gauntlet style gloves.

Other

Normal work clothing (long sleeved shirts and long pants) is recommended. Wear 100% cotton clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards

During product use, there is a risk of thermal burns.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

#### 9. Physical and chemical properties

Solid. **Appearance Physical state** Liquid.

> **Form** Solid. Color Dark brown to. Black

Odor Hydrocarbon-like. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available.

Initial boiling point and

Material name: GAF Coating Shafter

> 650 °F (> 343.33 °C)

boiling range

5895 Version #: 01 Issue date: 04-15-2015

SDS US

> 450.0 °F (> 232.2 °C) Cleveland Open Cup Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit -

upper (%)

Not available.

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Insoluble **Partition coefficient** Not available. (n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. Viscosity

Other information

Combustible IIIB estimated Flammability class

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under normal temperature conditions. Possibility of hazardous

reactions

Hazardous polymerization does not occur.

**Conditions to avoid** Do not overheat product. **Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** 

products

Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or

low molecular weight hydrocarbons. Hydrogen sulfide.

#### 11. Toxicological information

#### Information on likely routes of exposure

**Ingestion** Causes digestive tract burns.

**Inhalation** May cause irritation to the respiratory system. Skin contact Molten material will produce thermal burns. Molten material will produce thermal burns. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics Not available.

#### Information on toxicological effects

Not available. **Acute toxicity** Not available. Skin corrosion/irritation Serious eye damage/eye Not available.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available. Skin sensitization Not available. Germ cell mutagenicity Not available.

Carcinogenicity Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with

> certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body. IARC: occupational exposures to oxidized bitumens and their emissions during roofing are "probably

carcinogenic to humans" (Group 2A)

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Not available. Reproductive toxicity Specific target organ toxicity Not available.

- single exposure

Specific target organ toxicity

Not available.

- repeated exposure

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** This product has no known eco-toxicological effects.

Persistence and degradability Not available. **Bioaccumulative potential** Not available. Mobility in soil Not available. Other adverse effects Not available.

# 13. Disposal considerations

**Disposal instructions** Allow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

Waste from residues / unused products

Empty containers or liners may retain some product residues. This material and its container must

be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging No special precautions.

## 14. Transport information

DOT

**UN** number UN3257

**UN proper shipping name** Elevated temperature liquid, n.o.s. (ASPHALT)

Transport hazard class(es) 9 Class Subsidiary risk **Packing group** III

Special precautions for Not available.

user **IATA** 

> Not available. **UN number UN proper shipping name** Forbidden

Transport hazard class(es)

Class Forbidden

**Subsidiary risk** 

**Packing group** Not applicable.

**Environmental hazards** 

Special precautions for Not available.

user

Other information

Passenger and cargo

aircraft

Forbidden.

Cargo aircraft only

Forbidden.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

Material name: GAF Coating Shafter



**Further information** Shipping Marking: HOT. Transport by air is forbidden when shipped above 212°F (100°C).

## 15. Regulatory information

#### **US federal regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

# **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312** No

Hazardous chemical

SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act** Not regulated.

(SDWA)

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

# **US. Massachusetts RTK - Substance List**

Not regulated

# **US. New Jersey Worker and Community Right-to-Know Act**

Not regulated.

#### **US. Pennsylvania RTK - Hazardous Substances**

Not regulated.

# **US. Rhode Island RTK**

Not regulated.

# **US. California Proposition 65**

Not Listed.

## **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Material name: GAF Coating Shafter 5895 Version #: 01 Issue date: 04-15-2015

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Toxic Substances Control Act (TSCA) Inventory \*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 04-15-2015

**Version #** 

United States & Puerto Rico

**Further information** HMIS® is a registered trade and service mark of the NPCA.

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

Yes

materials or in any process, unless specified in the text.

SDS US 5895 Version #: 01 Issue date: 04-15-2015 6/6