SAFETY DATA SHEET



1. Identification

Product identifier Emulsion Base Stock 30 Pen

Other means of identification

Product Code 1627

Synonym(s) ASPHALT

Recommended use Asphalt Paving

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer: Tricor Refining, LLC.
Address: P.O. Box 5877
Bakersfield, CA 93388

24-hour Telephone

Number:

(661) 393-7110

CHEMTREC: 1-800-424-9300 (North America) 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Hazard symbol None.

Signal word

Hazard statement
Prevention
Response
Storage
Disposal

Not applicable.
Not applicable.
Not applicable.
Not applicable.

Hazard(s) not otherwise

classified (HNOC)

Molten asphalt presents a thermal hazard.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%	
ASPHALT		8052-42-4	<= 100	

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contactImmediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY.

Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of

the asphalt due to the risk of adhesion. Get immediate medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention or advice.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

Material name: Emulsion Base Stock 30 Pen 5732 Version #: 01 Issue date: 01-07-2015

Most important symptoms/effects, acute and delayed

Potential for severe thermal burns.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from

the chemical

Irritating and toxic gases or fumes may be released during a fire.

Special protective equipment and precautions for

firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may cause frothing.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up

Dike far ahead of spill for later disposal. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal.

7. Handling and storage

Precautions for safe handling

Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US.	ACGIH	Threshold	Limit Values
-----	--------------	------------------	---------------------

Material	Туре	Value	Form
Emulsion Base Stock 30 Pen	TWA	0.5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Che Material	mical Hazards Type	Value	Form
Emulsion Base Stock 30 Pen	Ceiling	5 mg/m3	Fume.
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses. Wear face shield if there is risk of splashes.

Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, Hand protection

wear gauntlet style gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended. Wear 100% cotton

clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards During product use, there is a risk of thermal burns.

Material name: Emulsion Base Stock 30 Pen 5732 Version #: 01 Issue date: 01-07-2015 General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Brown to black in color.

Physical state Liquid.

Form Semi-solid at ambient temperature

Color Black.
Odor Tar-like
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and

boiling range

> 700 °F (> 371.11 °C)

Flash point > 401.0 °F (> 205.0 °C) Open Cup

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available.

Vapor density > 5

Relative density 0.96 - 1.06

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature > 700 °F (> 371.11 °C)

Decomposition temperature Not available. **Viscosity** Not available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoid Incompatible materialsDo not overheat product.
Strong oxidizing agents.

Incompatible materialsHazardous decompositionUpon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or

products low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Ingestion Causes digestive tract burns.

InhalationMay cause irritation to the respiratory system.Skin contactMolten material will produce thermal burns.Eye contactMolten material will produce thermal burns.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

Material name: Emulsion Base Stock 30 Pen 5732 Version #: 01 Issue date: 01-07-2015

Acute toxicity

Skin corrosion/irritation

Serious eye damage/eye

Not available.

Not available.

irritation

Respiratory or skin sensitization

Respiratory sensitizationNot available.Skin sensitizationNot available.Germ cell mutagenicityNot available.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityNot available. **Specific target organ toxicity**Not available.

- single exposure

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity This product has no known eco-toxicological effects.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructionsAllow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

Waste from residues / unused products

Empty containers or liners may retain some product residues. This material and its container must

be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging No special precautions.

14. Transport information

DOT

UN number UN3257

UN proper shipping name Elevated temperature liquid, n.o.s. (ASPHALT)

Transport hazard class(es)
Class 9
Subsidiary risk Packing group III

Special precautions for Not available.

user

IATA

UN number Not available. **UN proper shipping name** Forbidden

Transport hazard class(es)

Class Forbidden

Subsidiary risk -

Packing group Not applicable.

Environmental hazards No.

Special precautions for Not available.

user

Other information

Passenger and cargo Forbidden.

aircraft

Cargo aircraft only Forbidden.

IMDG

UN3257 UN number

UN proper shipping name Elevated temperature liquid, n.o.s. (ASPHALT)

Transport hazard class(es) 9 Class **Subsidiary risk Packing group** III **Environmental hazards**

> Marine pollutant No.

Not available. **EmS** Not available. **Special precautions for**

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

DOT; IMDG



Further information Shipping Marking: HOT. Transport by air is forbidden when shipped above 212°F (100°C).

15. Regulatory information

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

ASPHALT (CAS 8052-42-4)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

ASPHALT (CAS 8052-42-4)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-07-2015

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: Emulsion Base Stock 30 Pen

5732 Version #: 01 Issue date: 01-07-2015